Home (http://www.ahernaustralia.com.au) / Elevating Work Platforms (http://www.ahemaustralia.com.au/equipment/elevating-work-platforms/) / Rough Terrain Scissor Lifts (http://www.ahernaustralia.com.au/equipment/elevating-work-platforms/rough-terrain-scissor-lifts/) / S2255RT



S2255RT

Max. Working Height:8.5m Overall Width:1.45m Platform Capacity:420kg Weight:2,360kg

Download Specifications (/wp-content/themes/xtreme-manufacturing/brochures/S2255RT.pdf)

Request Quote

Features	Specs	Warranty	Options	Turning Radius
Max Working Height			8.5m	
Max. Platform Height			6.5m	
Platform Size (stowed)			2.73m x 1.4m	
Platform Size (extended)			3.93m x 1.4m	
Extension I	Deck Lengt	h	1.2m	
Overall Len	gth		3.3m	
Overall Wid	lth		1.45m	
Stowed Hei	ght		2.3m	
Wheel Base)		2.0m	
Ground Cle	arance		260mm	
Platform Ca	pacity (SW	L)	420kg	
Max Wind Speed		45km/h		
Max Drive Height		6.5m		
Drive Speed Above 2.4m		0-0.8km/h		
Drive Speed	d Below 2.4	m	0-7km/h	
Gradeability	/		35%	
Exit/Entry A	angle		20°	
Inside Turn	ing Radius		2.5m	
Outside Tu	rning Radiu	ıs	4.75m	
Tyres			23" x 8.9" poly	filled
Axle		Articulating		
Power Sour	ce		Diesel engine	
Weight			2,360 kg	

Specifications subject to change without notice. Photos and diagrams on this website are for promotional purposes only. Refer to appropriate Snorkel operators manual for detailed instructions on the proper use and maintenance.