

Articulated & telescopic trailers

3522 A

Access on the move

Hydraulic outriggers and automatic leveling allow operation in under 30 seconds

Superior combination of industry leading capacity and outreach

Can be towed by a standard half-ton pickup truck - No commercial driver's license needed

Exceptional productivity

Air / water lines and 110V GFI protected power to the platform

COMPARE



TECHNICAL DATA

Working height	41 ft 9 in
Platform height	35 ft 9 in
Horizontal outreach (from centerline)	22 ft 6 in
Horizontal outreach (from edge of footpad)	17 ft 5 in
Up and over height	19 ft
Lift capacity	500 lbs
Length - stowed	16 ft 3 in
Width stowed	5 ft 6 in
Height stowed	6 ft 8 in
Platform size	4 ft 1 in x 2 ft 9 in
Turntable rotation	350° non-continuous
Jib - length	4 ft 3 in
Jib - Vertical Motion	150° (+70 / -80)
Tow speed rating	65 mph

Leveling capability	12.5 °
Tire size	ST 225/75 D15
Power source	4 x 6 V 245 amp-hr
Tongue weight (no options)	245 lbs
Weight (no options)	3400 lbs
Widest Point	11 ft 10 in
Widest Point	12 ft 2 in

STANDARD EQUIPMENT

MAIN OPTIONS

HAULOTTE SERVICES & WARRANTIES



HAULOTTE
FINANCIAL
SERVICES
(/SERVICE/HAULOTTE-
FINANCIAL-
SERVICES)



TECHNICAL
SUPPORT
(/SERVICE/TECHNICAL-
SUPPORT)



SPARE PARTS
(/SERVICE/SPARE-
PARTS)



TRAINING
(/SERVICE/TRAINING)








E-SERVICES
(/SERVICE/E-SERVICES)



MANUALS &
DOCUMENTATION
(/SERVICE/MANUALS-
DOCUMENTATION)



2D LIFE
(/SERVICE/2SECOND-
LIFE)



(<https://www.linkedin.com/company/haulotte-group>)